


BATTERY SWITCHES



Cole Hersee Battery Isolators

- Without Alternator Field Disconnect
- Installs in the same cutout and hole patterns as competitive switches
- High-impact, black molded cases are impervious to petroleum-based liquids for long life.

Order No	Mfg No	Amp Rating	List
108669	48070	70	\$80.88
108670	48120	140	\$151.43



Newmar Automatic Power Selector

The Automatic Power Selector (APS) is a solid state device which enables installation of a seamless, redundant power system for critical electronic loads. It selects the higher voltage of two isolated DC power sources and routes power to the load. Should one source falter or fail, the other will automatically supply the load with no transfer delay, operation continues uninterrupted.

Easy installation, two independent power sources are wired to the APS and routed in a single output to the vital load. Rugged, rust-proof anodized aluminum case.

Order No	Mfg No	List
107711	APS-70	\$129.60



Perko Main Battery Switch

- Ignition protected.
- Surface mounted in red plastic housing with large, black plastic knobs.
- Main disconnect "ON/OFF" switch.
- For use with systems under 50 volts.
- Rated for 250 amps continuous, 360 amps intermittent.
- 5-1/4" diameter x 2-5/8"

Order No	Mfg No	List
703473	9601DP	\$64.98



8501 & 8502



8503



Perko Battery Selector Switch

For use with two or more batteries and single or dual engine systems.

- Permits selection between batteries for starting and charging, or operation of both batteries in parallel.
- For use in systems under 50 volts.
- Rated for 250 amps continuous, 360 amps intermittent.
- For dual engines where two switches are required.

Order No	Mfg No	Type	List
700069	8501/DP	Standard	\$51.88

With Alternator Field Disconnect

Alternator Field Disconnect will interrupt the field current (reducing the possibility of damage) if turned "OFF" with the engine running.

Order No	Mfg No	List
340984	8503/DP	\$81.25



Perko Battery Selector Switch

- For use with two or more batteries and single or dual engine systems.
- Permits selection between batteries for starting and charging, or operation of both batteries in parallel.
- For use in systems under 50 volts.
- Rated for 450 amps continuous, 1200 amps intermittent (15 seconds on, 5 minutes off.)
- For dual engines two switches are required.

Order No	Mfg No	List
340995	8603/DP	\$216.50



Perko Heavy Duty Battery Disconnect Switch with Alternator Field Disconnect

- For use 6, 12, 24 and 32 volt marine electrical systems.
 - Capacity - rated 450 Amps continuous, 1200 Amps intermittent (15 seconds on, 5 minutes off).
 - For use in systems under 50 volts.
- Dimensions" 5-1/4" square; depth 3-3/8".

Order No	Mfg No	List
341006	9703/DP	\$206.05

BATTERY SWITCHES

**Blue Sea Systems e-Series Battery Switch Dual Circuit Plus™**

- Allows temporary isolation of house loads from engine circuits during engine cranking to protect sensitive electronics
 - Automatically combines battery banks during the charging cycle and isolates under discharge
 - 12/24 Volt auto ranging voltage input
 - Waterproof - Ignition protected.
 - Remote LED indicates various functions
 - Supports high-output alternators up to 120 Amperes
 - Activates from any charging source - alternators, battery chargers, or solar panels
- Continuous Rating: 120 Amperes DC
Intermittent Rating: 210 Amperes DC
Terminal Stud Size 3/8"-16 (accepts M10 ring terminal)
Maximum Cable Size 1/0 AWG
Agency Standards: ISO 8846 / Meets SAE J1171 external ignition protection requirements Width: 3.886"; Height: 3.502"

Order No	Mfg No	List
385769	7610	\$107.99

**Blue Sea m-Series (Mini) Battery Switches - Single Circuit On/Off Switch**

- Ignition protected - case design allows surface, front panel, or rear panel mounting.
- Isolating cover with snap-on sections protects rear contacts
- Inrush Rating: 0.25 sec (10 repeats): 1500 Amps
- DC Cranking Rating: 9.75 sec (10 repeats): 700 Amps
- DC Intermittent Rating: 5 min (UL 1107) 500 Amps
- DC Continuous Rating: (UL 1107) 300 Amps
- DC Maximum Voltage Rating 48 Volts DC

Order No	Mfg No	Description	Type	List
385714	6005	Single Circuit ON/OFF Battery Switch	With Key	\$31.47
385725	6006	Single Circuit ON/OFF Battery Switch	With Knob	\$31.47
386105	6011	Dual Circuit Plus™ Battery Switch	With Knob	\$52.44

**Blue Sea Systems HD-Series Battery Switch**

- Meets American Boat and Yacht Council (ABYC) requirements for battery switches.
- Ignition protected - safe for installation aboard gasoline powered boats.
- Case design allows surface or rear panel mounting.
- Accepts two 4/0 AWG (95mm²) battery cables.

Order No	Mfg No	Type	Amp Rating	List
386116	3000	Single Circuit On/Off	Intermittent: 900A; Continuous: 600A	\$95.02
386127	3002	Selector-4 Pos.	Intermittent: 700A; Continuous: 500A	\$98.94

**e-Series Battery Switch Single Circuit ON/OFF**

- Ignition protected - Safe for installation aboard gasoline powered boats
- Case design allows surface or rear panel mounting
- Meets American Boat and Yacht Council (ABYC) requirements for battery switches.
- Cranking amps max: 900
- Continuous amps max: 350
- Maximum voltage: 48 VDC

Order No	Mfg No	List
385747	9003e	\$45.29

**Blue Sea Systems e-Series Battery Switch Selector**

- Make-before-break contact design allows switching between battery banks without power interruption.
- Ignition protected - Safe for installation aboard gasoline powered boats.
- Case design allows surface or rear panel mounting.
- Meets American Boat and Yacht Council requirements for battery switches.
- Cranking amps rating: 900
- Continuous amps rating: 350
- Maximum volts: 48 DC

Order No	Mfg No	Description	List
385736	9001e	4 Position Selector	\$48.38
386138	9002e	4 Position Selector with Alternator Field Disconnect	\$53.53

**Blue Sea Systems Shore Power / Generator Selector Switch**

- Switches 2 - 120 or 230 Volt AC sources.
- Compact solution when circuit protection is provided elsewhere.
- Allows connecting one of two different AC sources to one circuit.
- Mounts in panels up to 0.16" (4.00mm) thick.
- Heavy duty industrial rated switch.
- Intuitive function - One hand operation.
- UL listed.
- Switches 120 or 230 Volt AC sources.
- 600 Volt AC max.
- Compact solution when circuit protection is provided elsewhere.
- Allows connecting one of several AC sources to one circuit.
- Mounts in panels up to 0.16" (4.00mm) thick.
- Heavy duty industrial rated switch.
- Intuitive function - one hand operation.

Order No	Mfg No	Amp Rating	Positions	List
386330	9009	30A	2 + Off	\$125.00
386341	9019	65A	2 + Off	\$350.00

BATTERY SWITCHES

GUEST



Guest Battery Selector Switch

- Single-pole, triple throw switch permits selection between two batteries, operation of both batteries in parallel, or complete disconnect of both batteries.
- Rated at 230 amps continuous or 345 amps momentary.
- 5-1/2" diameter, 2-5/8" high.
- Three mounting holes on 4-1/8" centers.
- Available with or without alternator field disconnect.

Order No	Mfg No	Alternator Field Disconnect	List
233197	2100	Yes	\$81.73
233198	2101	No	\$81.73

GUEST



Guest Extra Heavy Duty Diesel On/Off Switch

- A heavy-duty on/off switch with alternator field circuit disconnect for use where high amperage service is required, such as starting diesel engines.
- Rated at 600 amps continuous, 900 amps momentary.
- 5-1/2" square base x 3-1/2" high.
- Four mounting holes on 4-1/2" centers.

Order No	Mfg No	List
233202	2304A	\$258.35

GUEST



Guest Cruiser Series Universal Mount Switch

- Without Alternator Field Disconnect.
- Installs in the same cutout and hole patterns as competitive switches.
- High-impact, black molded cases are impervious to petroleum-based liquids for long life.
- Diameter: 5-1/2".

Order No	Mfg No	List
233169	2111	\$39.30



Hella Battery Master Switch

- For interrupting power (prevents theft and short-circuit during absence).
- Removable key.
- Max. load: 100A @ 12V continuous
- 500A @ 24V intermittent.
- Comes with a spare key.

Order No	Mfg No	List
231135	2843011	\$27.50

GUEST



Guest Heavy Duty Battery Selector Switch

- Heavy-duty switch is designed for the high amperage of marine service.
- Especially important for the large currents needed to start diesel engines.
- Rated at 360 amps continuous, 600 amps momentary, with alternator field disconnect.
- 5-1/2" square base x 3-1/2" high.
- Four mounting holes on 4-1/2" centers.

Order No	Mfg No	List
233201	2300A	\$184.50



Cole Hersee Master Disconnect Switch

- Protect against electrical fires, tampering, theft, etc. when equipment is unattended.
- Ignition protected.
- Ratings: 175 amps continuous
- 800 amps intermittent
- 15 seconds On, 5 minutes Off
- For 6-36 volt, DC electrical systems
- Silver contacts
- Brass case
- Chrome plated lever
- Brass mounting stem 3/4" diameter, 1-13/32" long.
- Two 3/8" diameter stud terminals
- Fits panels up through 15/16" thick.

Order No	Mfg No	List
108618	M284-01 BP	\$77.12

MARINE BATTERIES



Exide Nautilus Marine Batteries

Features and benefits

- Heavier cast-on strap - to withstand vibration.
- Stainless steel threaded and SAE posts.
- Calcium/calcium construction. Install it. Forget it.
- Enveloped polypropylene separators - for enhanced vibration resistance.
- Rigid polypropylene case and cover - for longer life in the marine environment.

(1) Limited Options: Instrumentation, Bilge Pump, Blower, Lighting.

(2) Electronic Options: Includes limited options and electronics (Loran, GPS, VHF, Depth and Fish Finder, Auto Pilot, Trim Tabs, Chart Plotter.)

(3) Trolling: Includes limited options and electric trolling motor, live wells.

(4) Full Options: Includes instrumentation, Bilge Pump, Blower, Lighting, all electronic options plus Down Riggers, Windlass, Inverter, Trolling Plates, Full Galley and trolling options.

(5) Full Deep Cycle: Operating full options without engine or generator support, i.e. relying solely on battery for power supply.

Batteries available by store pick-up only. Not UPS Shippable.



Order No	Mfg No	Cranking Amps	Application	Size	List
120012	EX16CLB	300	Kawasaki, Yamaha Jet Skis	6-15/16" x 4" x 6-1/8"	\$74.99
120010	XHDM24	625	O/B and I/B engines up to 300 hp + limited options (1)	11-3/8" x 6-3/4" x 10"	\$96.99
120007	XXHDM24	1000	O/B and I/B engine up to 750 hp + limited options (1) and electronic options (2)	11-3/8" x 6-3/4" x 10"	\$129.99
120125	NC24	630	All engines to 350 hp	11-3/8" x 6-3/4" x 10"	\$118.99
120009	NC27	730	All engines from 150 hp to 300 hp with electronics options (2) + trolling (3) or cycling.	13" x 6-13/16 x 10-1/4"	\$134.99
120008	NG27	670	All engines from 150 hp to 600 hp with full options (4) + trolling (3) + full deep cycle (5)	12" x 6-13/16 x 9-7/16"	\$163.99
120005	NG4D	1400	All diesel engines + all auxiliary items	20-11/16" x 8-11/16 x 9-7/8"	\$338.99
120006	NG8D	1725	All diesel engines + all auxiliary items	20-3/4" x 11-1/8" x 10-7/8"	\$406.99



Odyssey Marine Batteries

Phenomenal starting power and massive deep cycle reserve power in one battery!

Some batteries provide enormous cranking power. Others, deep cycle reserve power. The revolutionary ODYSSEY® battery is designed to do both.

How is this possible? The answer begins with flat plates made of 99.99% pure virgin lead - not lead alloy. Pure lead plates can be made thinner, so we can fit more of them in the battery. More ODYSSEY battery plates mean more plate surface area. And that means more power - twice as much as conventional batteries.

Batteries available by store pick-up only. Not UPS Shippable.



Order No	Mfg No	Type	Voltage	Cranking Amps	Length	Width	Height	Warranty	List
120003	PC1700T	Proup 27 Low Profile w ith 3/8" Cable Bolt	12	875	13.02"	6.62"	6.93"	4 Year Free Replacement	\$455.81
120015	PC1500MST	Group 24; Most Powerful on Market	12	880	10.85"	6.76"	7.82"	4 Year Free Replacement	\$379.78
120004	PC1200T	Trolling Motor	12	550	7.87"	6.66"	6.80"	3 Year Free Replacement	\$312.27
140389	PC625	PWC (Fits most models)	12	265	6.70"	3.90"	6.89"	2 Year Free Replacement	\$159.99



A/C Delco Voyager 12 Volt Batteries

Maintenance-free deep-cycle design allows batteries to provide long streams of power for extended periods.

- Heat-sealed covers provide added strength and rigidity.
- Rope handles with contoured handgrips for comfortable, convenient transport.
- Thermoplastic reinforced plates help increase protection against plate shorting and improve durability.
- Built-in "Green Eye" hydrometer.
- Both positive and negative grids are lead/calcium alloy to maximize corrosion resistance, increase cycle life, and reduce water consumption for battery durability.

Batteries available by store pick-up only. Not UPS Shippable.



Order No	Mfg No	Group	Cranking Amps	Dimensions	List
200544	M24MF	24	620	10.9" L x 6.8" W x 9" H	\$129.99
200545	M27MF	27	720	12.6" L x 6.8" W x 9" H	\$139.99
200583	MM30HMF	30	900	30.5" L x 6.7" W x 9.1" H	\$149.99

BATTERY BOXES • BATTERY TRAYS

attwood



Attwood Battery Holder Trays

Heavy-duty, non-corrosive black plastic. Includes adjustable height crossbar and two retaining bolts. Meets ABYC Standard E-10 and USCG requirements. Patented design. Install with #10 screws.

Order No	Mfg No	Group	Dimensions	List
244022	9090-5	24	10-5/8" x 6-3/4" x 8-3/4"	\$12.10
244021	41507-1	27	12-1/8" x 6-3/4" x 8-3/4"	\$13.40

DetMar
CORPORATION



Detmar Battery Holder

Keeps batteries securely in place. Prevents loosening of battery cables or spillage of battery acid. Easy to install. Adjustable height crossbar for secure fit. High-strength polypropylene cross piece with stainless steel hold down rods and fasteners.

Order No	Mfg No	List
233129	10-15-12S	\$16.05
233130	10-15-51S	\$16.05

ODYSSEY
THE EXTREME BATTERY



Odyssey Battery Trays

Order No	Mfg No	Fits	List
130505	PC1700-TRAY	13.30"L x 8.50"W x 6.75"H	\$40.00
140406	PC2150-TRAY	13.30"L x 8.63"W x 8.30"H	\$47.00
130504	0-01TRAY-PC1	8.90"L x 8.50"W x 6.60"H	\$40.00

T-H Marine



T-H Marine Battery Holder Trays

Battery holder fits into a limited space and is simple to install. The patented polypropylene hold down strap with positive locking quick disconnect buckle matched with a molded base that mounts with four (4) #10 pan head screws provides not only simple installation but changing or replacing batteries is quick and easy. Meets NMMA specs.

Order No	Mfg No	Group	List
302664	BH-24P-DP	24	\$14.61
302675	BH-27P-DP	27	\$14.61
730258	BH-31P-DP	29-31	\$14.63

TH Marine



TH Marine Battery Boxes

- Patented quick snap locking lid.
- Combo model has adjustable divider panel.
- Rugged molded poly.
- Resists acid, U/V and chemicals.

Order No	Mfg No	Fits	List
303438	BB-31P	Groups 27, 29, 31	\$17.75

attwood



Attwood Battery Boxes

All battery boxes meet U.S.C.G. spec. no. 183.420 as an OEM-installed battery hold down system. Polypropylene construction for total acid resistance. Hold-down straps resist 350 lbs. of force. Mounting hardware is included. Vented. Black.

Order No	Mfg No	Group	Dimensions	List
108159	9067-1	27	16-7/8"x9-5/8"x10-7/8"	\$14.20
244020	9065-1	24	14"x9-5/8"x10-5/8"	\$11.90

MOELLER



Moeller Roto-Molded Battery Boxes

Seamlessly designed to tackle the elements for long-life battery performance.

- Non-corrosive high-strength polyethylene construction resists chemicals and rust.
- Maintains tough properties with nominal 0.185" wall thickness on roto-molded (mixed linear-black) boxes.
- Complies to industry requirements and meets Coast Guard regulations (E10).

Order No	Mfg No	Dimensions	Fits	List
259004	042208	25.00" L x 14.87" W x 11.62" H	8D Battery Low Profile	\$118.25
259005	042209	24.37" L x 14.50" W x 14.12" H	8D Battery High Profile	\$124.33
259006	042204	23.87" L x 12.50" W x 13.5" H	4D Battery	\$118.65
259007	042212	17.50" L x 12.87" W x 11.25" H	Double Battery Box	\$113.35

BATTERY CHARGERS

GUEST




Guest Battery Pal™ Model 2602 Battery Charger

Storage/Maintenance Charger

A float charger that will keep your 12 volt batteries factory fresh without overcharging or boiling electrolyte. It supplies only the maintenance charge necessary to preserve battery life. Features an automatic safety shutoff and an LED indicator of proper operation.

Order No	Mfg No	List
233204	2602	\$62.88

GUEST



Guest Battery Charger Model 2611 Battery Charger Model 2611

A trolling motor charger for the boater who needs 10-12 hour full recovery. Ideal for systems with two 12 volt batteries or a 24 volt configuration. Comes prewired with a 6' AC cord and two 4' DC outputs. 10 amps output.

Dimensions: 7-3/4" W x 5-1/8" H x 2-1/16 D."

Weighs 6 lbs.

Order No	Mfg No	List
293440	2611A	\$191.68

GUEST

Guest 20 Amp Dual Trolling Motor Battery Charger

Total Amps: 20 Amps

Number of Outputs: 2

Amps per output: 10/10

Battery System: 2-12V or 1-24V

Output Voltage: 12VDC per output

DC Output: 2 -6' DC Outputs w/ring terminals

Input Voltage: 100-130VAC/50-60Hz

Input Connection: 6' AC Cord w/Connect Charge Pro

Dimensions: 9.60" x 7.0" x 2.63"

Weight: 8.0 Lbs.



Order No	Mfg No	List
293538	2620A	\$344.48

GUEST


Guest Bluewater Cruiser Chargers

Common Features:

- Efficient 3-stage charging with low AC draw.
- Provides and extra boost for engine starting.
- Compact, corrosion- and water-resistant case.
- Overload protection.
- Ignition protected.
- Reverse polarity protection. Automatic reset.

A 3-bank, 30 amp charger (20A/5A/5A) with a built-in ammeter. The advanced electronic switching technology lets you charge three banks quickly without the excess weight, long charging cycles and annoying hum of old style chargers.

9" W x 12-1/4" H x 7-1/4" D.



Order No	Mfg No	List
293527	2632A	\$677.00

GUEST



Intelligent Charging System Chargers

- The most advanced charging devices available! Fastest Charge with advanced micro-technology for maximum performance!
- The control center is a membrane covered panel, positioned for easy view of all functions and easily accessible to the user selectable buttons.
- Features easy to read LED Indicators of charge status, user selectable buttons to tailor the charge for specific battery types (AGM/Flooded or Gel) per output, and warning indicators to alert you before a serious problem.
- Electronics system is mounted on an anodized aluminum base to provide efficient heat dissipation and decreased weight.
- Circuits are coated in epoxy to protect sensitive electronic components from water or vibration and case is slotted on the sides to provide convection cooling of the anodized aluminum base plate while maintaining an IP65 Water Resistance standard.

Order No	Mfg No	Total Amps	Amps per Out	Input voltage	Output Voltage	Dimensions	List
293540	16102	12	6/6	12 + 12 or 24	12 VDC	2.4" X 4.9" X 7.0"	\$270.20
293551	16202	20	10/10	95-135 VAC, 50/60Hz, 5A	12 VDC	3.0" X 7.1" X 9.9"	\$438.23

GUEST



Remote Indicator Panel

Same Dual Output Remote Indicator used for both 16102 and 16202.

Order No	Mfg No	List
293562	16002-RI	\$55.45

GUEST



Guest ConnectCharge Inlet

For use with Guest Battery Chargers with Connect Charge Plug only.

Mounts to dash from rear with threaded locking ring or from the front with three screws through fact plate.

Eliminates rewiring, plug snaps into inlet locking tab.

Watertight lid protects AC plug.

Order No	Mfg No	List
293573	150CCI	\$25.58

BATTERY CHARGERS



Schumacher Ship 'N Shore Supreme Automatic Battery Charger

The ultimate charger for deep cycle, marine and marine starting batteries. Charges and maintains most Marine Group 24 to 30, 12-Volt wet-cell batteries.

- 12 amp charge is 20% faster than a 10 amp
- Fully Automatic-Automatically maintains the battery when fully charged. Resumes continuous charging when battery becomes discharged.
- Charges up to 16 volts and is suitable for Delco Voyager and similar batteries.
- Manual Operation.
- Microprocessor controlled - provides a 3-step charging system that includes float-mode maintaining and desulfation mode.
- LEDs - Power On, Reversed Hook-up, and Charging and Maintaining.

Order No	Mfg No	List
299500	SS120A-PE	\$109.99



Schumacher Fully Automatic Battery Charger

- 10/2 amp
- 10 amp rate.
- Reverse polarity protection.
- Fully automatic
- Easy to read meter with LED light that signals when fully charged.
- Charges 12-volt batteries
- 2 Amp trickle/maintenance charge turns on and off as needed.
- 2 year manufacturer's limited warranty.

Automatic circuit assures full charge, even on deep cycle batteries. Output shuts off completely at full charge, but turns back on as needed.

Order No	Mfg No	List
220322	SE-1275A	\$99.99



Schumacher Ship 'N Shore Charger/Maintainer/Tester

For 12 Volt Marine, Deep-Cycle, Automotive, AGM and Gel Cell Batteries.

15 Amp Fast Charge - charger monitors battery condition and adjusts charge rate downward to prevent battery damage; for car, truck, marine, RV, farm equipment, AGM, gel cell and deep-cycle batteries


10 Amp Fast Charge - self-adjusting charge rate for everyday charging needs and keeping your battery in peak condition

2 Amp Slow Charge - for charging small batteries and maintaining large ones; charges motorcycle, ATV, snowmobile and lawn tractor batteries

Easy-To-Read Digital Meter

System Test - helps diagnose problems with battery and charging system*

Order No	Mfg No	List
299537	SSC-1500A	\$109.99



Schumacher Battery Charger

- 10/2 amp
- 6/12-volt rate
- Excellent full-power charger for any size battery.
- 6" high x 9-1/2" wide x 8" deep.

Order No	Mfg No	List
220323	87102	\$90.00



Charles Marine 9000 Series Marine Ferroresonant Battery Chargers

The 9000 Series uses a self-regulating ferroresonant transformer devoid of any complicated switching circuits to charge up to three battery banks simultaneously. Built with rugged stainless steel enclosures and UL recognized, high-quality components to withstand the harsh marine environment. Accurately charge lead-acid batteries only. Features an easy-to-read ammeter to indicate rate of charge and ignition-protected components for safety. 12 VDC; 24 or 32VDC units available on special order basis. Dripshield included. 5-year warranty. Made in the USA.

Battery Type: Lead Acid

Battery Banks: 15 AMP = 2, All Others = 3

Charge Voltage: Single Stage 13.8V finish on 12 VDC, 27.6V finish on 24VDC

DC Output Voltage: 12V

AC Input Voltage: 95-140VAC

Frequency: 60Hz

Temperature Range: -25°C to 55°C

Safety Features: Thermal, over current, reverse polarity and ignition protected

Housing: Stainless Steel

Order No	Mfg No	Amp Rating	List
232998	CI1230A	30	\$837.02



Charles Marine 5000 Series 24VDC C-Charger Marine Electronic Battery Chargers

Approved to Marine UL's 1236 specifications.

20 Amp, 3 Bank

DC ammeter indicates the charge rate. AC and DC fuse protection. Ignition protected (USCG-33 CFR 183-410). Multi-step charging with temperature compensation. Restores up to 3 individual battery banks simultaneously. Internal temperature compensation automatically adjusts output to precisely charge batteries according to ambient conditions. Constructed of tough, anodized aluminum housing that stands up to the elements - including extreme heat, humidity and salt air. Circuit boards with UL recommended coatings provide the ultimate in environmental protection and hydrolyte stability. Exterior slots for easy mounting. Cooling fan operates during peak current demands.

Order No	Mfg No	Dimensions	List
234601	93-24205SP-A	13 1/4" x 9 1/2" x 3.7"	\$904.12

BATTERY CHARGERS • INVERTERS

ProMariner®
Advanced On-Board Chargers



ProMariner®
Advanced On-Board Chargers



ProSport Battery Chargers

- Distributed-On-Demand™ Technology
- Automatically charge and maintain engine crank battery while sensing and distributing 100% of the available charging amps to trolling motor or house bank battery.
- Fully charge and extend the life of your batteries with ProSport's multi-stage performance charge profiles. Automatically charges and conditions your batteries with a built-in safe maintenance mode for long or short term storage.
- 3 Charge Profiles - User selectable performance charge profiles for: Flooded(lead-acid)/STD AGM, GEL & High Performance(HP) AGM.
- High Visibility LED Status Center provides at-a-glance status of: AC Power, Charge Mode, Battery Type, and Ready/Maintenance Mode.
- Extruded Aluminum Housing for superior heat transfer and durability.
- Dynamic Thermal Output Control controls charging amps while maintaining the recommended charger temperature.
- Compact and rugged design, 100% waterproof and shockproof, dual inline DC safety fuses for trolling motor / accessory battery banks, dynamic thermal output control, over voltage, overload, overtemperature, reverse polarity, and ignition protection.

Prewired for easy installation

Order No	Mfg No	Voltage	Amps	Banks	List
186001	42006	12	6	1	\$129.99
186012	42012	12 or 24	12	2	\$189.99
186023	42021	12 or 24 or 36	20	3	\$262.00

ProMariner®
Advanced On-Board Chargers



ProTournament Multi-Bank Battery Chargers

- Advanced Electronic, Fully Automatic 3-Step Marine Battery Charger.
- Distributed On-Demand Charging - Automatically senses and distributes a full 10, 15 or 30 amps (model specific) to any one bank or combination of all banks.
- Faster Charging - 2 to 3 times faster than traditional battery chargers with true 3 step charging technology. Each step is electronically controlled for the fastest charge.
- Professional Performance - 100% battery charge guaranteed. 100% charging output with AC power as low as 90 VAC while using long extension cords at the dock, lodging site or home. Proven to condition and extend the life of your batteries.
- Compact Lightweight Design - Rugged Space Saver all aluminum housing is half the height of leading traditional chargers. Unit is not potted and is completely serviceable for lifetime of use under ProMariner's lifetime repair guarantee.
- Easy Operation - Pre-wired for easy installation. On-board Push-to-Test charge level and mode indicators. Internal battery selection-lead acid, gel or AGM compatible.
- True 3 Step Charging Electronically controlled for the Fastest Charge.
- Distributed On-Demand Charging will automatically distribute its full rated output of 10, 15 or 30 amps (model specific) to any one bank or combination of all battery banks. ProTournament distributes and uses every charging amp with no waste unlike other 2 and 3 bank chargers with an amp limit per bank.

Order No	Mfg No	Voltage	Amps	Banks	List
130231	51015	12 or 24	15	3	\$449.99
130230	51020	12 or 24	20	2	\$479.99

ProNauticP Series Battery Chargers

Up to 12 performance and precision 4-stage charging profiles: Charge, Condition, Maintain and Re-condition. Automatic power mode for 12 volt DC lighting and appliances. Factory set for Flooded (Lead Acid) batteries. AGM, GEL selectable. Auto-ranging (100-250 VAC/50-60Hz) global AC input with reduced harmonic distortion allowing all models to operate off a household power outlet connection. Consumes less power so more AC power is available on board. Automatically senses and distributes its maximum amp output to any one bank or combination of banks. Automatically programs conditioning time based on discharge stage of batteries. Automatically de-sulfates batteries after 21 days in the maintain mode, improving reserve power performance and extending battery life. After 72 hours of not seeing a load greater than 5 amps, float voltage will be lowered consuming less energy during storage periods (for flooded and sealed charge profiles). Real time indication of wiring faults or adverse conditions that may impact the operation of boat's charging system. Quiet operation. Automatic temperature compensation and built-in safety remote temperature probe included.

Order No	Mfg No	Amps	Banks	Voltage	List
186034	63120	20	3	12	\$422.00
186045	63130	30	3	12	\$516.00
186056	63140	40	3	12	\$560.00
186067	63180	30	3	24	\$890.00

Cobra
ELECTRONICS CORPORATION



Cobra Electronics Jumpstarter / Powerpack / Compressor

- Provides AC/DC portable power source anywhere and anytime.
- Runs household appliances up to 100 watts.
- Charge electric devices with USB port at 500mA.
- Super bright emergency light.
- Boost vehicles at 1200 Watts within seconds.
- 260 PSI air compressor.

Order No	Mfg No	List
389769	CJ1250	\$124.99

JUMPSTARTER - COMPRESSOR • BATTERIES



CPI400



CPI850



CPI1575



CPI2550

Cobra Electronics Power Inverters

It converts battery power to 120 V AC household power, allowing you to power up office equipment and household appliances from your vehicle. Cigarette lighter cord and direct-to-battery cables are included. This unit is ideal for laptops, 13" TVs, video games, CD players, DVD players, cellular phone chargers and much more!

Order No	Mfg No	Watts	List
389644	CPI480	400	\$69.99
389658	CPI880	800	\$99.99
389663	CPI1575	1500	\$249.99
389671	CPI2575	2500	\$399.99



Cobra Electronics Inverter Remote Control

Conveniently power on/off your Cobra inverter from a remote location. Includes 20 feet of cable.

This accessory works with the following inverter models:

- CPI 1000
- CPI 1500
- CPI 1550
- CPI 1575
- CPI 2500
- CPI 2550
- CPI 2575
- CPI M1500
- CPI M2200



Order No	Mfg No	List
389679	CPI A20	\$39.99



Cobra Electronics

Microport 130 Watt Power Inverter

- Provides household power on the go! Its swiveling 12 V DC accessory port plug converts your vehicle's cigarette lighter into 120 Volt AC household power.
- Power up office equipment and appliances under 130 watts, including most laptops.
- Also has a USB output, ideal for using/charging most small video games, an iPod®, a BlackBerry®, mobile phones, and many more USB devices. Its compact size and easy installation makes it ideal for travelers.



Order No	Mfg No	List
389615	CPI130	\$49.99



Eveready 6 Volt Lighting Battery

Screw type terminals on top of battery.

Order No	List
220247	\$7.29



Duracell Batteries

Order No	Mfg No	Size	Pack	List
220020	MN2400B4Z	AAA	4	\$5.99
220897	MN2400B-10Z	AAA	8	\$10.99
221859	MN24B16	AAA	16	\$22.95
220019	MN1500B4Z	AA	4	\$5.99
220878	MN1500B10Z	AA	8	\$10.99
221837	MN1500B16	AA	16	\$19.95
220017	MN1400B2Z	C	2	\$5.99
220805	MN1400R4Z	C	4	\$10.99
220016	MN1300B2Z	D	2	\$5.99
220793	MN1300R4Z	D	4	\$10.99
221826	MN13R8DW	D	8	\$19.95
220021	MN1604B1Z	9V	1	\$5.99
220885	MN1604B2Z	9V	2	\$10.99
221848	MN16B4DW	9V	4	\$19.95
220022	MN908	6V Lantern Spring Terminal	1	\$19.99



Duracell 3 Volt Lithium Batteries

Fits Monocular formerly carried by BOW.

Lithium battery 3 volt, 1400 mAh.

Size (mm): 34 x 16 x 16.

Order No	Mfg No	List
221585	DL123ABPK	\$8.95

D.S. HULL COMPANY, INC. • WHOLESALE MARINE DISTRIBUTOR • PHONE 954-463-4307 • TOLL FREE 1-800-437-1002